

**PART 1 - GENERAL****1.1 SUMMARY****A. WORK INCLUDED**

1. Factory pvc strip door unit with necessary mounting hardware.
2. Installation Manual.

**B. DESCRIPTION (APPLICATION)**

1. Door Size - Unit shall be designed for a door opening size of \_\_\_\_" wide x \_\_\_\_" high.
2. Chalfant PVC Strip Door Closure Model: \_\_\_\_\_.
3. Strip Door Mounting: Surface mount or Doorway mount (select one).
4. Percent of Overlap: 60% or 100% (select one).

**1.2 SUBMITTALS**

- A. General: Submit in accordance with Section 01 33 00.
- B. Product Data: Submit for pvc strip door.
- C. Submit dimensional detail.
- D. Submit specification.

**1.3 QUALITY ASSURANCE**

- A. Single Source Responsibility: Provide each component of individual pvc strip door per particular type by same manufacturer.
- B. Manufacturer Qualifications: Company specializing in manufacturing products specified in this Section with minimum ten years' experience.
- C. Installer Qualifications: Approved in writing by manufacturer.

**PART 2 - PRODUCTS****2.1 ACCEPTABLE MANUFACTURERS AND MODEL**

- A. PVC Impact Strip Door Closure as manufactured by Chalfant Sewing Fabricators, Cleveland, OH. Contact: <http://www.ChalfantUSA.com> for project quote.

**2.2 EQUIPMENT**

- A. COMPONENTS: PVC Strip Door shall consist of extruded PVC, non-toxic and FDA approved, with low temperature fl exibility to -20°-F or -40°-F. Mounting shall be doorway type or surface mount type hung from steel hardware angles. Full or 60% overlap, thickness and width of strips to be determined by model selection.
- B. WARRANTY: Unit shall include the manufacturers standard (1) one year warranty against defects in materials and workmanship on the remaining components.

**PART 3 EXECUTION****3.1 INSTALLATION**

1. Install in accordance with manufacturer's instructions.